

## Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 1.0AMP

Rating Current: 1.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘


Withstanding Voltage: AC 500V/Minute

溫度範圍: -40° C to +105° C








Temperature Range: -40° C to +105° C










Mating With/配對母座:



Dimension and tolerance list					
ITEM	A	B	C	D	H
Standard	3.00	4.00			1.7
Alternate	6.00				2.5



Dimension and tolerance list						
ITEM	A	B	D1	D2	H	
Standard	2.00	3.00			1.7	
Standard	4.00				2.5	
Alternate	6.00					



Dimension and tolerance list					
ITEM	A	B	C	D	H
Standard	2.00	4.00			1.7
Alternate	6.00				2.5

Dimension and tolerance list						
ITEM	B	C	D	W	H	
Standard	3.00				1.7	
Standard	4.00	0.1	7.5		2.5	
Alternate	6.00					

PIN HEADER

PH127X254-21

X

XX

XX

XXX

X

X

**Contact Shape:**  
P: Straight  
R: Right Angle  
S: SMT

**No. Of Pins Per Row**  
02~50P

**Contact Plating**  
Full Of Gold  
G0=0.8u"  
~  
G9=30u"  
S1=Ordinary Tin Plated  
S2=Matte Tin Plated  
S3=Tin-plated High-temperature

**Length Of Terminal**

**Packing**  
A: PE Bag  
R: Tape & Reel  
T: Tube  
D: Tube+CAP  
E: Tray

**Journal Number**  
1: Type1 (without Post)  
2: Type2 (with Post)