

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 2.0AMP

Rating Current: 2.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min

Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘

Withstanding Voltage: AC 500V/Minute


溫度範圍: -40° C to +105° C

Temperature Range: -40° C to +105° C




PH200-12RXXXXXXX3

L=24+2D4.0




PH200-12ZXXXXXXX1

L=B+2B+2




PH200-12ZXXXXXXX2

L=B+2B+2



PH200-12ZXXXXXXX3




L=B+C0.3+HW2





PH200-12ZXXXXXXX4

L=B+C0.3+HW2



Mating With/配對母座:







Dimension antitheses list			
ITEM	A	W	D
Standard	2.8	4.0	0.75
Alternate			





Recommended P.C.B Layout





Custom Width
高度可定制



Recommended P.C.B Layout



Recommended P.C.B Layout



TYPE1

TYPE2

Dimension antitheses list	
ITEM	B
Standard	2.0/3.0/4.0
Alternate	

Dimension antitheses list				
ITEM	B	C	D	W
Standard	2.0/3.0/4.0		0.10	4.50
Alternate				

PH200-12

X

Contact Shape:
R: Right Angle
Z: 90° SMT

XX

No. Of Pins Per Row
01~40P

XX

Contact Plating

Full Of Gold
G0=0.8u"
G9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

XXX

Length Of Terminal

X

Packing
A: PE Bag
R: Tape & Reel
T: Tube
D: Tube+CAP
E: Tray

X

Journal Number

1: Type1 (without Post)
2: Type2 (with Post)
3: Type3
4: Type4