

### Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 2.0AMP

Rating Current: 2.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min



Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘



Withstanding Voltage: AC 500V/Minute

溫度範圍: -40° C to +105° C







Temperature Range: -40° C to +105° C



Dimension alternatives list			
ITEM	A	B	H
Standard	2.80	2.0/3.0/4.0	1.5
Alternate			2.0



Dimension alternatives list				
ITEM	B	D	W	H
Standard	2.0/3.0/4.0	0.10	6.50	1.5
Alternate				2.0



Dimension alternatives list			
ITEM	A	B	D
Standard	2.80	2.0/3.0/4.0	0/0.75
Alternate			

Dimension alternatives list	
ITEM	B
Standard	2.0/3.0/4.0
Alternate	

PH200-13

X

XX

XX

XXX

X

X

**Contact Shape:**  
P: Straight  
R: Right Angle  
S: SMT  
Z: 90° SMT

**No. Of Pins Per Row**  
01~40P

**Contact Plating**  
Full Of Gold  
G0=0.8u"  
~  
G9=30u"  
S1=Ordinary Tin Plated  
S2=Matte Tin Plated  
S3=Tin-plated High-temperature

**Length Of Terminal**

**Packing**  
A: PE Bag  
R: Tape & Reel  
T: Tube  
D: Tube+CAP  
E: Tray

**Journal Number**  
1: Type1 (without Post)  
2: Type2 (with Post)