

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 3.00AMP

Rating Current: 3.00AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘

Withstanding Voltage: AC 500V/Minute


溫度範圍: -40° C to +105° C

Temperature Range: -40° C to +105° C



PH254-24PXXXXXXX1


L=A+B+C




PH254-24RXXXXXXX1

L=A+B+C+D+1.25


Mating With/配對母座:



PIN HEADER



Dimension anttheses list			
ITEM	A	B	C
Standard	3.00	4.5/6.0	
Alternate			



Dimension anttheses list				
ITEM	A	B	C	D
Standard	3.00	4.5/6.0		1.20
Alternate				

PH254-24

X

XX

XX

XXX

X

1

Contact Shape:
P: Straight
R: Right Angle

No. Of Pins Per Row
02-40P

Contact Plating
Full Of Gold
G0=0.8u"
~
G9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

Length Of Terminal

Packing
A: PE Bag
R: Tape & Reel
T: Tube
D: Tube+CAP
E: Tray