

Specifications

備注(Remark)

1. 材料(Material)

膠芯:PA9T/LCP+30% G.F UL94V-0, 顏色:黑色

Housing:PA9T/LCP+30% G.F UL94V-0,

Color:Black

端子:磷銅

Contact:Phosphor Bronze

2. 特性(characteristics):

額定電流:1.0AMP

Rating Current:1.0AMP

接觸阻抗:20mΩ Max

Contact Resistance:20mΩ Max

絕緣阻抗:1000MΩ Min


Insulating Resistance:1000 MΩ Min

耐電壓: AC 500V/分钟

Withstanding Voltage:AC 500V/Minute

溫度範圍: -55° C to+125° C

Temperature Range: -55° C to+125° C



BF100-23XXXX440X1





BF100-23XXXX440X2



Mating With/配對公座:




Mating Pin Long
(建議接插增長度)
B=4.00mm



Mating With(配)
B569



BF100-23XXXX440X3





Mating With(配)
B569

BF100-23XXXX440X4







FEMALE HEADER



Recommended P.C.B Layout



Recommended P.C.B Layout



BF100-23

XX

XX

440

X

X

No.Of Pins Per Row
02~50P

Contact Plating

Full Of Gold
G0=0.8u"

G9=30u"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

Packing

A:PE Bag

R:Tape & Reel

T:Tube

D:Tube+CAP

E:Tray

Journal Number

1:Type1(without Post)

2:Type2(with Post)

3:Type3

4:Type4