

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30% G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30% G.F UL94V-0,

Color: Black

端子: 磷銅

Contact: Phosphor Bronze

2. 特性 (characteristics):

額定電流: 1.0AMP

Rating Current: 1.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘


Withstanding Voltage: AC 500V/Minute

溫度範圍: -55° C to +125° C


Temperature Range: -55° C to +125° C




BF227-15SXXX340X1



BF227-15SXXX340X2






BF227-15SXXX340X3




BF227-15SXXX340X4


Mating With/配對公座:




FEMALE HEADER




Recommended P.C.B Layout






TYPE 1




Recommended P.C.B Layout





TYPE 3



Recommended P.C.B Layout



TYPE 2



Recommended P.C.B Layout

TYPE 4

BF227-15

X

XX

XX

340

X

X

Contact Shape:
S:SMT

No. Of Pins Per Row
02~50P

Contact Plating
Full Of Gold
G0=0.8u"
G9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

Packing
A:PE Bag
R:Tape & Reel
T:Tube
D:Tube+CAP
E:Tray

Journal Number
1:Type1(without Post)
2:Type2(with Post)
3:Type3
4:Type4