

### Specifications

**備注 (Remark)**

**1. 材料 (Material)**

膠芯: PA9T/LCP+30% G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30% G.F UL94V-0,

Color: Black

端子: 磷銅

Contact: Phosphor Bronze

**2. 特性 (characteristics):**

額定電流: 1.0AMP

Rating Current: 1.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘


Withstanding Voltage: AC 500V/Minute

溫度範圍: -55° C to +125° C

Temperature Range: -55° C to +125° C



BF127X254-22PXXXX570X1





BF127X254-22SXXXX570X1




BF127X254-22SXXXX570X1



**Mating With/配對公座:**



Recommended P.C.B Layout



Recommended P.C.B Layout



FEMALE HEADER

**BF127X254-22**

**X**

**XX**

**XX**

**570**

**X**

**X**

**Contact Shape:**  
P: Straight  
S: SMT

**No. Of Pins Per Row**  
02~50P

**Contact Plating**  
Full Of Gold  
C0=0.8u"  
~  
G9=30u"  
S1=Ordinary Tin Plated  
S2=Matte Tin Plated  
S3=Tin-plated High-temperature

**Packing**  
A: PE Bag  
R: Tape & Reel  
T: Tube  
D: Tube+CAP  
E: Tray

**Journal Number**  
1: Type1 (without Post)  
2: Type2 (with Post)