

### Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30% G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30% G.F UL94V-0, Color: Black

端子: 磷銅

Contact: Phosphor Bronze

2. 特性 (characteristics):

額定電流: 2.0AMP

Rating Current: 2.0AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分钟


Withstanding Voltage: AC 500V/Minute

溫度範圍: -55° C to +125° C

Temperature Range: -55° C to +125° C





BF200-41XXXX635X1




BF200-41XXXXHX1



Mating With/配對公差:



Recommended P.C.B Layout



Recommended P.C.B Layout



FEMALE HEADER

BF200-41

XX

XX

635

X

1

No. Of Pins Per Row  
02~40P

Contact Plating

Full Of Gold

C0=0.8u"

~

C9=30u"

S1=Ordinary Tin Plated

S2=Matte Tin Plated

S3=Tin-plated High-temperature

Packing

A: PE Bag

R: Tape & Reel

T: Tube

D: Tube+CAP

E: Tray