

### Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 2.00AMP

Rating Current: 2.00AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min

Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘



Withstanding Voltage: AC 500V/Minute

溫度範圍: -40° C to +105° C


Temperature Range: -40° C to +105° C



Mating With/配對母座:







B200-22PXXXXXX1







B200-22SXXXXXX1

### BOX HEADER B



Dimension antitheses list		
ITEM	A	C
Standard	3.0	
Alternate		



Dimension antitheses list		
ITEM	C	W
Standard		7.80
Alternate		

B 200 - 22

X

XX

XX

X

X

1

**Contact Shape:**  
P: Straight  
S: SMT

**No. Of Pins**  
06~64P

**Contact Plating**  
Full Of Gold  
C0=0.8u"  
~

C9=30u"  
S1=Ordinary Tin Plated  
S2=Matte Tin Plated  
S3=Tin-plated High-temperature

**Insulator Colour**  
B: Black  
G: Grey

**Packing**  
A: PE Bag  
R: Tape & Reel  
T: Tube  
D: Tube+CAP  
E: Tray