

Specifications

備注 (Remark)

1. 材料 (Material)

膠芯: PA9T/LCP+30%G.F UL94V-0, 顏色: 黑色

Housing: PA9T/LCP+30%G.F UL94V-0, Color: Black

端子: 黃銅

Contact: Brass

2. 特性 (characteristics):

額定電流: 3.00AMP

Rating Current: 3.00AMP

接觸阻抗: 20mΩ Max

Contact Resistance: 20mΩ Max

絕緣阻抗: 1000MΩ Min


Insulating Resistance: 1000 MΩ Min

耐電壓: AC 500V/分鐘


Withstanding Voltage: AC 500V/Minute

溫度範圍: -40° C to +105° C


Temperature Range: -40° C to +105° C




B254-21PXXXXX1



B254-21RXXXXX1





B254-21SXXXXX1







B254-21SXXXXX2



Mating With/配對母座:





Recommended P.C.B Layout






Recommended P.C.B Layout



TYPE 1 TYPE 2



Recommended P.C.B Layout



L	
6P~8P	10P~64P
4.00	4.40

BOX HEADER B

B254 - 21

X

Contact Shape:
P: Straight
R: Right Angle
S: SMT

XX

No. Of Pins
06~64P

XX

Contact Plating
Full Of Gold
G0=0.8u"
~
G9=30u"
S1=Ordinary Tin Plated
S2=Matte Tin Plated
S3=Tin-plated High-temperature

X

Insulator Colour
B: Black
G: Grey

X

Packing
A: PE Bag
R: Tape & Reel
T: Tube
D: Tube+CAP
E: Tray

X

Journal Number
1: Type1 (without Post)
2: Type2 (with Post)