

Specifications

Wafer

備注 (Remark)



1. 材料 (Material)

膠芯: PA66 UL94V-0



Housing: PA66 UL94V-0

端子: 黃銅

Contact: Brass



WTB2000-PR3-XX



Poles	Dimensions (mm)		
	A	B	C
2	2.00	6.00	2.50
3	4.00	8.00	2.50
4	6.00	10.00	3.50
5	8.00	12.00	5.50
6	10.00	14.00	7.50
7	12.00	16.00	9.50
8	14.00	18.00	11.50
9	16.00	20.00	13.50
10	18.00	22.00	15.50
11	20.00	24.00	17.50
12	22.00	26.00	19.50
13	24.00	28.00	21.50
14	26.00	30.00	23.50
15	28.00	32.00	25.50
16	30.00	34.00	27.50

Wafer

備注 (Remark)



1. 材料 (Material)

膠芯: PA66 UL94V-0



Housing: PA66 UL94V-0

端子: 黃銅

Contact: Brass



WTB2000-2PV2-XX



Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
04	2.00	6.00	26	24.00	28.00
06	4.00	8.00	28	26.00	30.00
08	6.00	10.00	30	28.00	32.00
10	8.00	12.00	32	30.00	34.00
12	10.00	14.00	34	32.00	36.00
14	12.00	16.00	36	34.00	38.00
16	14.00	18.00	38	36.00	40.00
18	16.00	20.00	40	38.00	42.00
20	18.00	22.00	42	40.00	44.00
22	20.00	24.00	44	42.00	46.00
24	22.00	26.00			

Wafer

備注 (Remark)



1. 材料 (Material)

膠芯: PA66 UL94V-0



Housing: PA66 UL94V-0

端子: 黃銅

Contact: Brass



WTB2000-2PR2-XX



Poles	Dimensions (mm)		Poles	Dimensions (mm)	
	A	B		A	B
04	2.00	6.00	26	24.00	28.00
06	4.00	8.00	28	26.00	30.00
08	6.00	10.00	30	28.00	32.00
10	8.00	12.00	32	30.00	34.00
12	10.00	14.00	34	32.00	36.00
14	12.00	16.00	36	34.00	38.00
16	14.00	18.00	38	36.00	40.00
18	16.00	20.00	40	38.00	42.00
20	18.00	22.00	42	40.00	44.00
22	20.00	24.00	44	42.00	46.00
24	22.00	26.00			

W

WAFER